



TECHNICAL INFORMATION

PAS/N

*****PAS/N*** Papilio Aqua-Slide**

Item #: PAS/N

Media: Precoated Water Slide Paper

Media Type: Laser printer or Copiers

Color: Clear / Transparent

Printers: B&W Laser Printers and Minolta

Magicolor Color Laser

DO NOT USE THIS PAPER IN HP LASER PRINTERS

1) Copy/Print A MIRROR IMAGE on to the PAS paper using a late model B&W personal copier, laser printer or Minolta Magicolor color laser. First adjust the contrast and colors and print/copy on regular paper. If using the ALPS printer, select regular paper. (For Alps printers we recommend our PAS/2 decal paper) (The transparency selection and other options may work as well.) Do NOT use photo quality ribbons if you are using Alps MD series printer.. When the test print looks OK, then print on the PAS paper.

2) Cut out the image with scissors. Dip in warm water (not hot). The paper will roll up and then straighten out again.

3) When the film starts to loosen from the paper, place the paper on the substrate to be decorated, FACE DOWN, the film touching the substrate and the paper side up. Then slide THE PAPER away leaving the film behind. Now the image will no longer be a mirror image. This is opposite to using decal.

4) Work out air bubbles with decal squeegee and let dry. It is important to remove all water and air.

5) When dry you can spray over the image using fixative spray available at most hobby stores. This will also make the decal stick better to the surface.

Note: As the film is transparent (not white), white will only appear on white surface, or white paint must be applied to the surface first. Some ALPS printers can print white. Printing out a regular image (not a mirror image) is also an option. Then you will slide the image (the water decal) OFF the paper and on to the surface of the item to be decorated. Be careful not to tear the film. Remember if you use this option the decal film will not protect the Alps ink.

PAS Decals can be coated (finished) using most clear finishing including clear epoxy, urethane or most other solvent based finish if a pplied face down.

Note:

1)You can iron images on to mouse-pads and similar substrates using the PAS paper/film and then release the paper when cold, using water. But it can not be used to decorate T-shirts.

2)Do not attempt to copy or print on sheets of PAS paper you have already cut holes in or cut pieces off. This can cause paper jam and possible damage to your equipment

3)For best paper economy arrange images that fit on the whole sheet, print on regular paper to test and then print on the whole surface of the PAS paper the first time.

4)This paper has not been tested in, nor is it recommended for use in high speed industrial type copiers/printers. Even though this paper has been tested on most late model office copiers and laser printers the user must determine the compatability of this paper with his own equipment. In some cases, if the paper jams and stays in contact with the hot fusing roll (in a copier or laser printer) damage can occur. In case of paper jam, REMOVE the PAS paper immediately.

Do not use this paper in RICOH FT series copiers.

Store the paper in a closed plastic zipper-bag in a cool and dry location.

High humidity and heat may affect the shelf life of this product

HPS Mfg P.O. BOX 855 Rhome TX 76078-0855 Tel: 817-489-5249

www.papilio.com