



PAPILIO Inkjet Media

Printing and Application Instructions

New Formula July 2002

This paper can be used to make clear decals.

To make white decals use our white inkjet vinyl.

For improved result the paper in this kit can now be use with Krylon Clear Acrylic spray or use our LLA UV spray or use clear decal fixative.

To make CLEAR/TRANSPARENT decals

- 1) Copy/Print on to the White Paper
- 2) Spray the decal using clear acrylic spray. Follow instructions on spray can. If you are using our clear decal fixative then Let the first coat (the puddle) sit on the decal for about 20 seconds and gently move the puddle around on the decal the first few seconds then wait. Then without applying any pressure on the decal use the foam pad to move the excess fluid off and over the edge of the paper on to a piece of cardboard and discard, leaving a thick and even coating on the image. Let dry for at least 8 hours or over

Read all instructions carefully before use. If you hold the narrow (thin) end of the foam pad the maximum pressure you can put on the decal is the gentle force that slightly bends the foam pad. Decal solutions are not to be used by minors. Use the clear decal solution in a well ventilated area. Do not print with high resolution when making "white" decals as the white fixative may then make the ink "the colors" run or bleed together. White and clear decal fixative may be difficult or impossible to remove from cloths or other items when dry. Do not thin the clear decal fixative.

HPS PO Box 855
Rhome TX 76078-0855
E-mail: sales@papilio.com

For complete updated list of our media and to order on line go to WWW.PAPILIO.COM
As a precaution do not use this kit if you are pregnant or nursing a baby.

Item # IAS8511K	5 sheets pack
Media	Pre-coated Water Slide Decal
Media Type	Inkjet
Color	Makes Clear Decals
Printers	Most Desk Top Inkjet

night. Second coat may not be needed at all.

Applying the decal.

Cut out the image with scissors. Dip in warm water (not hot). The paper will roll up and then straighten out again.

When the film starts to loosen from the paper, place the paper on the substrate to be decorated, and slide the paper from under the decal.

Work out air bubbles with decal squeegee and let dry. It is important to remove all water and air.

Note: White clouds may appear in the clear film (may be slightly opaque) However the decal will turn completely clear over the period of 24 to 48 hours.

DO NOT cut out the decal first and then apply the solution as the edges of the paper will absorb the liquid making it impossible later to slide the decal off the paper.

Disclaimer: We have tested our media in various personal inkjet printers with good results. The user of this paper/film must determine the suitability of this product before beginning production, using his equipment and method of application. The Sellers and Manufactures maximum obligation shall be to replace paper/film that has been found to be defective. Neither the manufacturer nor the seller shall be held liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper/film.