



Printing and Application Instructions

This vinyl can be used outdoors without lamination.

Lamination is recommended for greatly extended life.

- 1) Copy/Print on to the coated side of the media using compatible Inkjet Printer.
DO NOT print with high resolution (or heavy ink deposit) as this may not work well and/or cause the color to run when you apply water to the vinyl.
- 2) To prevent a paper jam, make sure the vinyl is not bent or warped or corners folded BEFORE loading. Loading by hand ONE SHEET at the time (pressing FF/Ready) is a way to make sure it loads correctly.
- 3) Let the ink dry for at least 20 minutes.
- 4) To condition the vinyl label for outdoor use (after you print on it) flush the whole label with generous amount of water. This is done to prevent bleeding of the colors that can happen if the label gets only partly wet for the first time and the water stays on (does not run off)
- 5) When gluing a vinyl label to any surface, clean the substrate and remove residual grease, soot or dust.
- 6) It is not recommended (on larger labels) to remove all the back paper before installing. It's better to remove the paper from a small area at one end first such as a 1/2" vertical strip at the left hand or right hand edge.
- 7) Line up your label. When the position looks

NOTE: To extend UV resistance of Inkjet media HPS offers overlamine with built in UV barrier. When using self adhesive media, note that any adhesive may become difficult to remove over time. If you want to use self adhesive media on automobiles or other items where you don't want the label to become permanent or difficult to remove after long time, then we recommend our selection of media with removable adhesive.

HPS PO Box 855
Rhome TX 76078-0855
sales@papilio.com
www.papilio.com

General: If you are working with 4.25" x 11" vinyl you can try removing all the backing material and then use the technique described above.

HYAZ™ Inkjet Media

Waterproof White Matte Vinyl

| | |
|------------------|---------------------------------|
| Item # | WVF8511GW 10 sheets pack |
| Media | Self Adhesive Vinyl |
| Media Type | Inkjet |
| Color | White Matte |
| Printers | Most Desk Top |
| Type of Adhesive | Permanent. Removable 1-2 weeks. |

correct, let the label make contact with the surface on the edge where you removed the back paper.
8) Now bend the label back and carefully remove the rest of the protective back paper, and glue the label down working from the end you glued first. Then work your way towards the other end holding that end away from the surface. You can use your finger or a sponge and only press down (glue) a small area each time to prevent trapping air bubbles. Do not use excessive pressure when working the label in this way because you may smudge the ink.
To make the label scratch resistant use overlamine. Make test before starting production for resale, using your equipment and method of printing.
Using overlamine is highly recommended and will greatly extend the life of the label if it is used outdoors.

Disclaimer: We have tested our media in various personal inkjet printers with good results. The user of this paper/film must determine the suitability of this product before beginning production, using his equipment and method of application. The sellers and manufactures maximum obligation shall be to replace paper/film that has been found to be defective. Neither the manufacturer nor the seller shall be held liable for any injury, direct or consequential, arising out of the use of, or inability to use this paper/film.